



# MATERIAL SAFETY DATA SHEET

Bailey® 1030 Primer for PVC/CPVC/ABS Plastic Pipes

Date Revised: SEP 2016  
Supersedes: JUN 2016

## SECTION 1 - IDENTIFICATION

1.1 - **TRADE NAME:** Bailey® 1030 Low VOC Primer for PVC/CPVC/ABS Plastic Pipe

1.2 - **SUPPLIER:** Taizhou G-Good Adhesives Co., Ltd.  
Shiniu Village, Yanjinag Town, Linhai City, Zhejiang,  
P.R.China  
Tel. 86-576-85696851

**MANUFACTURER:** Taizhou G-Good Adhesives Co., Ltd.  
Shiniu Village, Yanjinag Town, Linhai City, Zhejiang,  
P.R.China  
Tel. 86-576-85696851

## SECTION 2 - RISK/HAZARD IDENTIFICATION

|                     |                      |                   |                             |                  |                        |
|---------------------|----------------------|-------------------|-----------------------------|------------------|------------------------|
| Acute Toxicity:     | Health<br>Category 4 | Acute Toxicity:   | Environmental<br>None Known | Flammable Liquid | Physical<br>Category 2 |
| Skin Irritation:    | Category 3           | Chronic Toxicity: | None Known                  |                  |                        |
| Skin Sensitization: | NO                   |                   |                             |                  |                        |
| Eye:                | Category 2           |                   |                             |                  |                        |

GHS LABEL:



Signal Word:

WHMIS CLASSIFICATION: CLASS B, DIVISION 2  
CLASS D, DIVISION 1B

| Hazard Statements                       | Precautionary Statements   |
|---|--|
| H225: Highly flammable liquid and vapor | P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking                                     |
| H319: Causes serious eye irritation     | P261: Avoid breathing dust/fume/gas/mist/vapors/spray  |
| H332: Harmful if inhaled                | P280: Wear protective gloves/protective clothing/eye protection/face protection                            |
| H335: May cause respiratory irritation  | P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing |
| H336: May cause drowsiness or dizziness | P403+P233: Store in a well ventilated place. Keep container tightly closed                                 |
| H351: Suspected of causing cancer       | P501: Dispose of contents/container in accordance with local regulation                                    |
| EUH019: May form explosive peroxides    |  |

## SECTION 3 - CHEMICAL COMPOSITION

|                           | CAS#     | CONCENTRATION | SYMBOL | R phrases   | S phrases   | Exposure Limit Value |
|---------------------------|----------|---------------|--------|-------------|-------------|----------------------|
| Methyl Ethyl Ketone (MEK) | 78-93-3  | 19 - 31%      | F Xi   | 11-36-66-67 | 2-7-9-16-51 | 200 PPM              |
| Cyclohexanone             | 108-94-1 | 10 - 30%      | Xn     | 10-20       | 7-29        | 25 PPM Skin          |
| Acetone                   | 67-64-1  | 25 - 35%      | F Xi   | 11-36-37-38 | 23-26-33-39 | 750 PPM              |
| Tetrahydrofuran (THF)**   | 109-99-9 | 15 - 25%      | F Xi   | 11-19-36/37 | 7-16-29-33  | 200 PPM              |

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing. \* Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372). # indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

## SECTION 4 - FIRST AID MEASURES

**Contact with eyes:** Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.  
**Skin contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.  
**Inhalation:** Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.  
**Ingestion:** Rinse mouth with water. Give 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Seek medical advice immediately.  
**Likely Routes of Exposure:** Inhalation, Eye and Skin Contact  
**Acute symptoms and effects:**  
**Inhalation:** Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passages.  
**Eye Contact:** Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.  
**Skin Contact:** Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.  
**Ingestion:** May cause nausea, vomiting, diarrhea and mental sluggishness.  
**Chronic (long-term) effects:** Category 2 Carcinogen

## SECTION 5 - FIREFIGHTING MEASURES

5.1 **Suitable Extinguishing Media:** -Dry chemical powder, carbon dioxide gas, foam, Halon, water fog.  
5.2 **Unsuitable Extinguishing Media:** -Water spray or stream.  
5.3 **Exposure Hazards:** -Inhalation and dermal contact  
5.4 **Combustion Products:** -Oxides of carbon, hydrogen chloride and smoke  
5.5 **Protection for Firefighters:** -Self-contained breathing apparatus or full-face positive pressure airline masks.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 **Personal precautions:** -Keep away from heat, sparks and open flame.  
-Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.  
-Prevent contact with skin or eyes (see section 8).  
6.2 **Environmental Precautions:** -Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.  
6.3 **Methods for Cleaning up:** -Clean up with sand or other inert absorbent material. Transfer to a closable steel vessel (Metal or Polyethylene).  
6.4 **Materials not to be used for clean up:** -Liquid(s)

## SECTION 7 - STORAGE AND HANDLING

7.1 **Handling:** -Avoid breathing of vapor, avoid contact with eyes, skin and clothing.  
-Keep away from ignition sources, use only electrically grounded handling equipment and ensure adequate ventilation/fume exhaust hoods.  
-Do not eat, drink or smoke while handling.  
7.2 **Storage:** -Store in ventilated room or shade between 5°C and 44°C (40°F-110°F) and away from direct sunlight.  
-Keep away from ignition sources and incompatible materials: caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers and isocyanates.  
-Follow all precautionary information on container label, product bulletins and solvent cementing literature.

## SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

8.1 **System Design:** If ventilated cabinet, enclosure or fume hood is necessary, average airflow should be at least 100 FPM (50.8cm/sec).  
8.2 **Monitoring:** Maintain breathing zone airborne concentrations below exposure limits (see section 2).  
8.3 **Personal Protective Equipment (PPE):**  
**-Eye Protection:** Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.  
**-Skin Protection:** Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.  
Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.  
**-Breathing Protection:** Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.  
With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

|                        |   |                     |   |
|------------------------|---|---------------------|---|
| 9.1 Appearance:        | Clear or Purple, thin liquid  |                     |   |
| 9.2 Odor:              | Ethanol similar to Acetone  |                     |   |
| 9.3 pH:                | N.A.P.  |                     |   |
| 9.4 Boiling Point:     | 57° to 67°C(133° to 151°F) based on first boiling component: Acetone      |                     |   |
| 9.5 Flash Point:       | -6°C to -4°C(25°F) T.C.C.   |                     |   |
| 9.6 Auto Flammability: | 321°C(609.8°F): Acetone   |                     |   |
| 9.7 Vapor Pressure:    | 143 mm Hg @ 20°C(68°F): Acetone   |                     |   |
| 9.8 Solubility:        | Solvent portion completely soluble in water. Resin portion separates out. |                     |   |
| 9.9 Other Data:        | Vapor Density   | >2 (Air=1)          | Specific Gravity @ 23°C±2° (73°F±3.6°)Typical 0.845±0.040 |
|                        | Evaporation Rate  | >1.0 (BUAC=1)       | Flammability Limits LEL: 2.1%                             |
|                        | Viscosity   | Variable by product | (percent by volume) UEL: 13%                              |

#### SECTION 10 - STABILITY AND REACTIVITY

|  |   |
|--|---|
| 10.1 Stability:                        | Stable under recommended storage conditions. (See Section 7)  |
| 10.2 Conditions to avoid:              | Keep away from heat, sparks, open flame and other ignition sources.                                       |
| Effects:                               | When forced to burn, this product gives out carbon monoxide, carbon dioxide, hydrogen chloride and smoke. |
| 10.3 Materials to avoid:               | Caustics, ammonia, inorganic acids, chlorinated compounds, strong oxidizers.                              |
| 10.4 Hazardous decomposition products: | None in normal use. See item 10.2 for reactivity/combustion effects.                                      |

#### SECTION 11 - TOXICOLOGICAL INFORMATION

##### 11.1 Acute symptoms and effects:

|                             |  |
|-----------------------------|--|
| Inhalation:                 | Severe overexposure may result in nausea, dizziness, headache. Can cause drowsiness, irritation of eyes and nasal passage.                       |
| Eye contact:                | Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctiva inflammation on contact with the liquid. |
| Skin contact:               | Liquid contact may remove natural skin oils resulting in skin irritation. Dermatitis may occur with prolonged contact.                           |
| Ingestion:                  | May cause nausea, vomiting, diarrhea and mental sluggishness.  |
| Chronic(long-term) effects: | None known to humans.  |

#### SECTION 12 - ECOLOGICAL INFORMATION

|                    |  |
|--------------------|--|
| 12.1 Mobility:     | In normal use, emission of volatile organic compounds (VOC's) to the air takes place. Typically at a rate of ≤ 550 Grams/Liter.. Minimal other adverse effects include possible ground water contamination from release to soil, sewers, drains or water course. |
| 12.2 Degradability | Biodegradable  |
| 12.3 Acourmulation | Minimal to none.   |

#### SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers or water courses. Empty containers should be air dried before disposing.

#### SECTION 14 - TRANSPORT INFORMATION

|  |                                      |                                |                          |
|--|--------------------------------------|--------------------------------|--------------------------|
| 14.1 UN Number:                                  | UN1993                               | 14.7 ADR/RID CLASSIFICATION:   |                          |
| 14.2 UK Road & Sea Freight (IMO) Classification: | 3.2                                  | Class:                         | 3.5c                     |
| 14.3 Substance Classification Number:            |                                      | Item number:                   |                          |
| 14.4 Class:                                      | 3                                    | 14.8 ICAO/IATA CLASSIFICATION: |                          |
| 14.5 Packing Group:                              | II                                   | Class:                         | 3                        |
| 14.6 Proper Shipping Name:                       | Flammable Liquid, n.o.s.             | Sub-Risk:                      | None                     |
| PGR (if applicable)                              | Tetrahydrofuran, Methyl Ethyl Ketone | Packing Group:                 | II                       |
|  |                                      | Proper Shipping Name:          | Flammable Liquid, n.o.s. |

#### SECTION 15 - REGULATORY INFORMATION

|                                       |  |   |
|---------------------------------------|--|---|
| 15.1 Precautionary Label Information: | Highly Flammable, Irritant   |   |
| 15.2 Symbols:                         | F,Xi   |   |
| 15.3 Risk Phrases:                    | R-10 Flammable<br>R-11 Highly Flammable<br>R-20 Harmful by inhalation  | R-36/37/38 Irritating to eyes, respiratory system and skin.<br>R-65 Repeated exposure may cause skin dryness or cracking.<br>R-67 Vapors may cause drowsiness and dizziness.          |
| 15.4 Safety Phrases:                  | S-2 Keep out of reach of children<br>S-7 Keep container tightly closed when not in use<br>S-9 Keep container in a well-ventilated place.<br>S-16 Keep away from sources of ignition. No smoking. | S-24/25 Avoid contact with skin and eyes.<br>S-29 Do not empty into drains.<br>S-33 Take precautionary measures against static discharges.<br>S-51 Use only in well ventilated areas. |

#### SECTION 16 - OTHER INFORMATION

##### 16.1 Specification Information:

|                                |   |
|--------------------------------|---|
| Department issuing data sheet: | G-Good, Research and Development Department |
| Contact name:                  | David                                       |
| E-mail address:                | <sales@g-good.com.cn>                       |

|                                       |   |
|---------------------------------------|---|
| 16.2 Training necessary:              | Yes, training in practices and procedures contained in solvent-cementing literature |
| 16.3 Reissue date/reason for reissue: | SEP 2016 / Change format to conform with GHS requirements                           |
| 16.4 Intended use of product:         | Primer for bonding/cementing PVC/CPVC/ABS plastic pipes and fittings                |

16.5 This product is intended for use by skilled individual sat their own risks. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.